

Portable Air Conditioners



MODEL	2AP7500A	2AP10000A	2AP13000A	2APP13000	2AP14000A	2APP14000
Product Description	7,500 BTU Portable Air Conditioner	10,000 BTU Portable Air Conditioner	13,000 BTU Portable Air Conditioner	13,000 BTU Portable Air Conditioner with heat pump	14,000 BTU Portable Air Conditioner	14,000 BTU Portable Air Conditioner with heat pump
Power supply (V-Ph-Hz)	115V/60Hz	115V/60Hz	115V/60Hz	115V/60Hz	115V/60Hz	115V/60Hz
Cooling Capacity(W)	5150BTU/1510W	6250 Btu/1830w	8000BTU/2345W	8000BTU/2345W	10400 Btu/3048	10400 Btu/3048
SACC Cooling Capacity	5000 Btu/1465W	6000BTU/1758W	8000BTU/2345W	8000BTU/2345W	10000BTU/2930W	10000BTU/2930W
Cooling Input Power(W)	700	890	1060	1060	1210	1210
Cooling Input Current(A)	6.1	7.9	9.2	9.2	10.6	10.6
CEER (Btu/W.H)	6.20	6.61	7.22	7.22	7.94	7.94
Designed CEERsd	6.10	6.51	7.22	7.22	7.83	7.83
Coverage area(Sq Ft)	200	300	400	400	500- 600	500 - 600
Heat pump / Element	/	/	/	Heat pump	/	Heat pump
Heating Capacity(W)	/	/	/	11000BTU/3220W	/	3900
Heating Input Power(W)	/	/	/	1050	/	1100
Heating Input Current(A)	/	/	/	9.0	/	9.5
COP (W/W)	/	/	/	2.79	/	11.9
Cooling Test Condition(Ashare 128)	35°C/28.3°C	35°C/28.3°C	35°C/28.3°C	35°C/28.3°C	35°C/28.3°C	35°C/28.3°C
(Ashare 128) (Btu/h)	7500	10000	13000	13000BTU/3810W	14000	14000
EER (Btu/Wh)	9.9	10.1	10.4	10.4	10.2	10.2
(Ashare 128) Input Power(W)	753	980	1250	1250.0	1370	1370
(Ashare 128) Input Current(A)	6.6	8.6	11	11	11.9	11.9
Heat pump / Elecment	/	/	/	Heat pump	/	Heat pump
Heating Test Condition	/	/	/	21°C/15.6°C	/	21°C/15.6°C
Heating Capacity(W)	/	/	/		/	3900
Heating Input Power(W)	/	/	/		/	1100
Heating Input Current(A)	/	/	/		/	9.5
COP (W/W)	/	/	/		/	11.9
Rated Power(W)	950	1150	1400	1400	1365	1365
Rated Current(A)	9.4	10.0	14.0	14.0	13.3	13.3
UL Rated Current (A)	8.5	11.8	12.0	12.0	12.0	12.0
Indoor air flow (Hi/Med/Lo) (m3/h)	280/- /220	320/290/260	360/320/280	360/320/280	530/490/450	530/490/450
CFM	165/-/130	188/171/153	212/184/165	212/184/165	312/288/268	312/288/268
Moisture Removal(L/h) Cooling	1.08	1.25	1.64	1.64	1.6	1.6
Sound (Hi/Med/Lo)(dB(A))	54/51	54/51/49	54/51/49	54/53/52	54/51/49	54/51/49
Refrigerant type	R32	R32	R32	R32	R32	R32
Product Dimensions (in)	12.60*26.38*12.60	17.32D x 27.36W x 12.8H	17.5D x 28.15W x 14.56H	17.5D x 28.15W x 14.56H	17.7D x 29.3W x 15.6H	17.7D x 29.3W x 15.6H
Product Weight (lbs)	49.28	53.46	65.56	70.2	74.58	75.24
Packing Dimensions (in)	12.6D x 26.4W x 12.6H	19.1D x 34.9W x 14.17H	19.1D x 35W x 16.9H	19.1D x 35W x 16.9H	19.76D x 34.65W x 18.2H	19.76D x 34.65W x 18.2H
Shipping Weight (lb)	55.9	62.26	73.7	75.8	86.0	86.7
UPC Code	850012484318	850012484325	850012484332	850012484356	850012484349	850012484363