

SHOPFAN

PLUG AND PLAY COMFORT



SERIOUS AIR. SIMPLE SETUP.

ShopFan isn't just easy—it's effortless. Pre-wired and plug-in ready, this DIY-friendly powerhouse installs fast and delivers big air to garages, workshops, and gyms. ShopFan was built for hardworking spaces that need premium airflow at a practical price. Marked with official Big Ass Fans branding, it brings a bold look that stands for quality and performance in every spin. No fluff, no fuss—just serious airflow without the complications.

BENEFITS

- Improves energy efficiency
- Variable speed operation
- Redundant, industry-leading safety systems
- Fully wired and factory tested
- Branded hub and VFD cover
- 1 year warranty



KEY FEATURES

- 100–120V with 3-prong plug
- Mounts to I-beams, purlins, bar joists, and solid beams
- Six aluminum airfoils with winglets
- 14' diameter
- Sealed helical gearbox and industrial motor



FOR MORE INFORMATION


Visit **bigassfans.com/contact-us** or call **877.BIG.FANS** to learn how ShopFan can transform your space.



SHOPFAN

TECHNICAL SPECIFICATIONS





Wired Standard Control Height: 4.86 in. (123 mm) Width: 4.54 in. (115 mm) Depth: 1.3 in. (29 mm)

Technical Specifications								
Diameter	Max Weight ¹	Max Speed	Input Power and Required Breaker	Motor Horsepower	Airfoil Clearances ²	Max Operating Temperature		
14 ft (4.3 m)	172 lb (78 kg)	70.4 RPM	100–120 VAC, 50/60 Hz, 1 Ф, 15 А	1.0 hp (0.75 kW)	2 ft (0.6 m) on sides 5 ft (1.5 m) below ceiling	104°F (40°C)		

Construction Features							
Airfoils	Motor and Onboard VFD	Mounting	Multi-Point Safety ³	Colors			
Six patented Powerfoil airfoils (mill finish) Powerfoil winglets eliminate wind noise (BAF yellow)	Industrial-grade motor and gearbox feature inline helical-cut gears for efficient, durable, and reliable operation; lubricated for life with synthetic oil Onboard, pre-wired NEMA 4X VFD housed in spacious ABS/PVC-based enclosure with built-in heatsink 15 ft (4.6 m) VFD power cord plugs into standard electrical outlet	Standard upper mount installs to I-beams and bar joists 2 ft (0.6 m) extension tube Optional kits allow for mounting to solid beams and purlins	Double safety cable system, airfoil retainers, hub safety clips, Grade 8 hardware, and fire relay	Silver and Yellow			

Wired Standard Control				
Construction	Controls			
Made from durable UV-resistant materials	On/Off and variable speed control			
Rated IP55 Intuitive touchscreen interface	Password protection Powered by fan drive			

Wired Standard Control











Weight does not include mount or extension tube.
Measure the distance from the tip of the winglet to the ceiling or major obstruction.
The fire relay must be wired during install if required by local code.



USA **BIGASSFANS.COM** 877.244.3267

CANADA BIGASSFANS.COM 844.924.4277

AUSTRALIA BIGASSFANS.COM/AU 1300.244.277

SINGAPORE BIGASSFANS.COM/SG 65.6709.8500