

## **EnviroKlenz Everyday Odor Eliminator:**

For use with vacuum:

1) Vacuum up loose debris from the area to be treated. 2) Remove other debris by blotting the area with a wet towel. 3) Soak the treatment area with clean, warm water. 4) Rinse the towel and soak up any excess water leaving the area damp. 5) Pour EnviroKlenz on the prepared area. 6) Spread the EnviroKlenz into the area, working it deeply into the carpet. 7) Pour fresh, clean water over the EnviroKlenz treated area until saturated. 8) Apply pressure to the area by standing/walking on the treated area. 9) Allow the EnviroKlenz formulation to remain on the area for 15 minutes. 10) Use a clean, absorbent towel to soak up any excess water. Repeat 2-3 times to aid drying. 11) Allow the area to completely dry. Note: It may take 24 hours or longer for the area to be completely dry. 12) Once dried, vacuum up the residue. Brushing the area can aid removal. Vacuum until residue has been completely removed by visual examination.

### **Rug:**

The same basic process as for the carpet can be used. One significant advantage is that both side of the rug can be treated if necessary. In that event, treat one side completely, then repeat the process on the other side of the rug. Synthetic fibers may require additional contact time with the EnviroKlenz. If it is a small rug and can be placed inside a small

bucket or container, you can fill the bucket with enough warm water to fully cover the rug, then add the EnviroKlenz product (about 1/2 cup per gallon of water), mix the water and EnviroKlenz, then submerge the rug. Periodically provide some agitation. Let it soak for 24 hours.

### **Upholstery:**

Always test the surface for color fastness. The product is best used on upholstery when diluted at a 1:1 ratio with fresh clean warm water. The product can be dabbed on the affected area with a clean cloth or sponge or sprayed via a pump sprayer. You want to achieve a thin visible coating of the EnviroKlenz product. Let it sit for 15 minutes, then extract out with a water extractor and fresh water. Allow to air dry. If the item is machine washable, you can wash/rinse it to remove the EnviroKlenz.

### **Mattress:**

Depending on the odor contamination level, you can either use diluted or undiluted product. If the odor is strong use a more concentrated amount, for mild odors the product could be diluted 1-part EnviroKlenz to 4 parts fresh, clean, warm water. Pre-clean the area by removing as much physical debris as possible. Soak up any excess liquid, if applicable. Slowly pour about 1 cup of the EnviroKlenz (diluted or undiluted) directly onto the site(s) of

contamination and allow it to soak in for about 5 minutes. Add an additional 1/2 cup of EnviroKlenz. After about 15 minutes soak up the excess water and allow to dry. Once dry remove any visible dried EnviroKlenz by brushing it with a dry cloth or towel before lightly vacuuming.

### **Car Interior:**

Car interiors have a variety of surfaces and each type may need to be managed separately. Test each surface type for ease of removal before applying the product to the whole surface. EnviroKlenz typically does not damage surfaces, but it can be difficult and time consuming to remove, especially from porous or textured surfaces. Remove floor mats and any other surface that can be treated more easily outside the vehicle. Vacuum the vehicle to remove as much physical debris as possible. For the hard surfaces use diluted EnviroKlenz at a ratio of 1 part EnviroKlenz to 4 parts fresh, clean, warm water. Apply a light, but visible coating to surfaces using a clean towel or sponge. For the soft surfaces, make sure you have a water extractor available for removal. Apply EnviroKlenz (diluted at a 1:1 ratio with fresh, clean, warm water) to the soft surfaces and allow it to soak in. Use extreme caution on leather surfaces. Pay attention to all surfaces. Odors do linger in the headliner and around the window gaskets and this is especially true for cigarette smoke odors. Allow the EnviroKlenz to contact the surfaces for at least 15 minutes. Longer is

okay, but you don't want the product to fully dry as it is easier to remove when still wet. Use the water extractor on all the soft surfaces and uses a sponge to clean up the hard surfaces. Allow the surfaces to dry. You may need to repeat the removal process on certain surfaces.

### **Wood Flooring:**

The product can be used on sealed wood flooring or on the subfloor below wood flooring. Diluted EnviroKlenz (1 part EnviroKlenz to 4 parts fresh, clean, warm water) can be sponged or mopped onto the surface. Please note that EnviroKlenz residing in cracks and crevasses will be more difficult to remove. Allow at least 15 minutes of contact time, but do not allow the EnviroKlenz to dry on the surface, as it will be much more difficult to remove the visible residue.

### **Tile Flooring:**

Use EnviroKlenz diluted at a 1 part EnviroKlenz to 4 parts of fresh, clean, warm water. Sponge or mop the product onto the tile. Do not allow to fully dry. The residue is difficult to remove from unsealed grout or dark grout. Use clean water to remove via sponge or mopping. It may take multiple steps to fully remove the EnviroKlenz without there being visible residue.

### **Spray Applications:**

EnviroKlenz can be used and sprayed onto a variety of surfaces inside and outside. Use 1 to 4 diluted EnviroKlenz and place inside a clean pressurized pump sprayer (like garden sprayer). Some applications where the product can be sprayed and just left in place (invisible residue is not a problem) include:

- - Treating urine contaminated cement or pavers
- - Artificial grass cleaning and deodorization
- - Apply to contaminated subfloors before new flooring is installed for odor prevention
- - Treating insides of large garbage or waste containers
- - Walls and floors of unfinished basements, cellars, and crawl spaces