



F600

OPERATING
&
FILTER REPLACEMENT
DIRECTIONS

TO BEGIN USING YOUR **AIRPURA**

Inspect the exterior of your Airpura to verify there is no damage from shipping. If any damage is noted, please follow the instructions from the distributor returns policy.

Wipe the unit with a damp cloth to remove any dust from packaging


Plug the unit into a regular grounded 110 volt outlet

Turn on the unit to MAX and allow it to run for a few minutes

Set the variable speed control to the level you wish

The most efficient way to use your Airpura for regular air quality maintenance is to run it at a low speed **24 hours a day 7 days a week.**

Maintain a humidity level of below 40% at all times in your home.



FILTER MAINTENANCE AND REPLACEMENT

Ensure regular maintenance/replacement of filters

The Prefilter

Can be vacuumed from the exterior of the unit once a month or more often. Should be replaced at least after 12 months of use

To vacuum the Prefilter


Use the brush attachment on your vacuum cleaner
Vacuum slowly around the mesh surface of the filter chamber

IMPORTANT SAFETY NOTE


Please ensure air purifier is turned OFF when plugging into a power source. Failure to do so may result in motor potentially stalling and/or burning.



Poly Prefilter 600 2-pack
12 months



**18 lbs, Impregnated Carbon
Filter 35% potassium
permanganate carbon, 65%
coconut shell**
24 months



**HEPA 600RVHU filter
(99.97% efficient)**
3 to 5 years
F614: HEPA 14 filter
(99.99% efficient)

Technical specifications

Odors, airborne chemical control

18 lbs enhanced Carbon
13"H x 13.25"OD x 9"ID

Particle removal

40 ft² true HEPA
(Measured 1 side only)
12 pleats per inch
Pleats warm rolled with separators

Air Flow 560 cfm

More cfm than any other
home unit available

Prefilter

570 in² x 1 in

Housing

Powder coat steel

Size

23 in x 15 in

Weight

45 lbs total

Watts

120 on high / 40 on low

Sound Level


28.1 db on low (at 6 feet)
62.3 db on high (560 cfm)
(Room Level 25.1)

ETL certified

Conforms to CSA C22.2
no 113 ANSI / UL 507

Possible upgrade :

UV Germicidal Lamp, 20 Watt



Air purifiers models and filter configurations

	Prefilter	Particle
Alternates	Cotton Prefilter TarBarrier Prefilter	
Upgrade		HEPA 14 filter (99.99% efficient @ 0.3 microns) ULPA filter (99.9999% efficient@ 0.1 microns)

To open the filter chamber



To close the filter chamber

