

# HESSAIRE PUMP INSTALLATION INSTRUCTIONS

## WARNING

- DISCONNECT ELECTRICAL POWER TO COOLER BEFORE INSTALLING OR SERVICING PUMP.
- PUMP INSTALLATION MUST COMPLY WITH COOLER MANUFACTURER'S SPECIFICATIONS AND APPLICABLE ELECTRICAL AND BUILDING CODES.
- USE ONLY IN UPRIGHT POSITION.

1) Before you begin replacing your evaporative cooler pump, turn off and unplug your unit.

2) Carefully remove the back panel and media from your cooler by removing the 2 Phillip screws and slide up then pull down and out on the panel

3) Remove the control panel in the center or left side (depending on the model of your unit) on the upper portion of the cooler

4) Take note or a picture of the pump function connection before disconnecting the pump

5) Remove the green hose from the pump adapter


6) Unscrew and remove the old or defective pump from the lower portion of your unit

7) Once removed, place the new pump with hose connector, ensuring that the suction cups are on the bottom portion of the pump. Insert the screw back into place so that the pump is stabilized completely in the cooler

8) Connect wire connector to the control panel as the original pump was connected and ensure you secure the cord to the side of the unit using zip ties to ensure the cord does not interfere with the fan blade

9) Connect the green hose to the hose connector

10) Once you have completed all steps you then can return the back panel and media to the back of the cooler and ensure your control panel is back into place



If you have any issues or problems installing the pump please visit [www.Hessaire.com](http://www.Hessaire.com), select parts, and how to change a pump for an instructional video

