Transform Health Care Environments

UPDATED Bio Cart HEPA 10 & Bio Cart HEPA-UVC 15





Bio Cart 15 Cutaway

Promotes effortless facility maintenance

Quick set-up and breakdown

Ease of Operation

Features intuitive, user-friendly design

Specs subject to change without notice.

FACILITATES EASY MAINTENANCE AND OPERATION

Experience maintenance made simple with the Bio Cart HEPA 10 and Bio Cart 15 HEPA-UVC PREMIUM. Designed with health care professionals in mind, these portable containment units redefine ease of maintenance in any health care setting.

Their user-friendly designs facilitate effortless operation, while their innovative features allow for quick and efficient maintenance. Whether it's the Bio Cart 10's telescoping ladder or the Bio Cart 15's integrated video camera and monitor, every element is thoughtfully designed to make your maintenance tasks smoother and more manageable. With the Bio Cart series, ensure your health care facilities remain in peak condition with minimal effort.

VISIT BIOCARTS.COM FOR MORE INFORMATION

Bio Cart Specifications





Air Scrubber Fan	880 CFM@300 watt • 62 Db at maxspeed
	reachIng up to 6 air changes per minute
Bellows	Fire retardant black and yellow vinyl that Is 3
	Inches high when collapsed with a total unit
	height of 10 feet when extended
Cable Pass Through	Cable feed through
Caution Sign	Externally visible LED "IN USE" light
Construction	Extruded aluminum frame and walls made of
	white melamine with a thermal coating skin
	provide a durable and easy to clean surface
Control Panel	Control panel with air scrubber on/off control
	and manual lift up/down switch and Remote
	Control for ease of use. Also turns on the air
	scrubber and power
Document Protection	Document holder on door
Door	Aluminum frame with a white thermal bonded
	skin that Is 32 Inches W, 73 Inches H. Locks from
	Inside or outside
Filtration	Electrostatic disposable pads pre-filter, and a
	99.97% 0.3 Micron HEPA filter
Ladder	13 ft. telescoping aluminum ladder that meets
	OSHA requirements for electrical safety and
	class A rated for 300 lbs.
Lighting	Interior white LED lighting
Power Cord	25 ft. long power cord with grounded plug
Power Outlets	Duplex power outlet
Size Collapsed	73 L, 32 W, 77 inches H
Size Fully Extended	73 L, 32 W, 120 Inches H
Top Lifting Mechanism	Power lift with foam seal at top, for ceilings from
	7 ft to 10 ft. 2 in. hight
Weight	450 lbs, with ladder and all air scrubber filters
1	installed
Wheels	4 Inches dia. x 2 Inches wide non-marking. Two
	with wheel brakes and two with swivel locks
Windows	Front and back windows
UPC	850040074963
SKU	FG0283
31/0	1 40200

Specs subject to	o change	without	notice.
------------------	----------	---------	---------

6 air changes per minute Bellows Fire retardant black and yellow vinyl that Is 3 Inches high when collapsed and with a total unit height of 15 feet when extended Cable Pass Through Catle feed through Caution Sign Externally visible LED "IN USE" light Construction Extruded aluminum frame and walls made of white melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Fire retardant black and yellow vinyl that Is 3 Inches high when collapsed and with a total unit height of 15 feet when extended Cable Pass Through Caution Sign Externally visible LED "IN USE" light Construction Extruded aluminum frame and walls made of white melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Fully Extended 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Mult1-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Air Scrubber Fan	880 CFM@300 watt • 62 Db at maxspeed reaching up to
high when collapsed and with a total unit height of 15 feet when extended Cable Pass Through Caution Sign Externally visible LED "IN USE" light Construction Extruded aluminum frame and walls made of white melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document Protection Document holder on door Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended Top Lifting Mechanism Multl-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		6 air changes per minute
feet when extended Cable Pass Through Cable feed through Caution Sign Externally visible LED "IN USE" light Construction Extruded aluminum frame and walls made of white melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism Multi-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Bellows	Fire retardant black and yellow vinyl that Is 3 Inches
Cable Pass Through Caution Sign Externally visible LED "IN USE" light Construction Extruded aluminum frame and walls made of white melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		high when collapsed and with a total unit height of 15
Caution Sign Externally visible LED "IN USE" light Construction Extruded aluminum frame and walls made of white melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		feet when extended
Construction Extruded aluminum frame and walls made of white melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Cable Pass Through	Cable feed through
melamine with a thermal coating skin provide a durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Caution Sign	Externally visible LED "IN USE" light
durable and easy to clean surface Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Construction	Extruded aluminum frame and walls made of white
Control Panel Control panel with manual lift up/down switch and Remote Control for ease of use Document Protection Document holder on door Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism Multl-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		melamine with a thermal coating skin provide a
Remote Control for ease of use Document Protection Document holder on door Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		durable and easy to clean surface
Document Protection Document holder on door Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism Mult1-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Control Panel	Control panel with manual lift up/down switch and
Doorside Aluminum frame with a white thermal bonded skin that Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism Multi-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		Remote Control for ease of use
Is 29 Inches W, 62.5 Inches H. Locks from Inside or outside Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		Document holder on door
Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Doorside	Aluminum frame with a white thermal bonded skin that
Filtration Electrostatic disposable pads pre-filter, and a 99.97% 0.3 Micron HEPA filter Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		Is 29 Inches W, 62.5 Inches H. Locks from Inside or
Interlock HEPA door switch for fan and UVC/UVGI Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism Multl-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		0.00.00
Interlock Ladder. Is ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord Size Collapsed Size Collapsed Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight Wheels Hinches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum UPC 850040074970	Filtration	Electrostatic disposable pads pre-filter, and a 99.97%
Ladder. 15 ft. telescoping aluminum ladder that meets OSHA requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
requirements for electrical safety and class A rated for 300 lbs. Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Ladder.	' ~
Lighting Interior white LED lighting Power Cord 25 ft. long power cord with grounded plug Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Power Cord Power Outlets Duplex power outlet Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Power Outlets Size Collapsed 73 L, 32 W, 77 inches H. Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Size Collapsed 73 L, 32 W, 77 inches H. 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Size Fully Extended 73 L, 32 W, 182 Inches H. Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		• •
Top Lifting Mechanism MultI-stage power lift with foam seal at top, for ceilings from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
from 7 ft. to 15 ft. 2 in. height. Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Weight 480 lbs with ladder and all air scrubber filters installed Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Top Lifting Mechanism	
Wheels 4 Inches dia. x 2 Inches wide non-marking. Two with wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
wheel brakes and two with swivel locks Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Window Front and back windows Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Wheels	ű
Camera/Monitor Rear mounted camera with front mounted viewing monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
monitor Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970		
Portable Vaccum 3 Gallon Wet/Dry Vac UPC 850040074970	Camera/Monitor	ŭ
UPC 850040074970		
	Portable Vaccum	·
SKU FG0284	UPC	850040074970
	SKU	FG0284

Division of D.P.L. Enterprises Inc.

3868 East Post Road, Las Vegas, Nevada 89120, (702) 454-5515, FAX (702) 454-5225

Website: www.air-care.com; E-mail: cs@Air-Care.com

Specifications subject to change without notice.