

Spec Sheet

4400A (GFI #5961)	
Type	Fan-Assist Evaporative Humidifier
GPD (Based on 120° F Plenum Temperature)	19
Dimensions (Inches; HxWxD)	15.75 x 16.63 x 6.75
Weight (Pounds)	10.4
Fan dB	48
Replacement Vapor Pad*	GA35 (GFI#7902) (Replace 1-2 Times Per Season)
Home Size (Square Feet)	Up To 4,400
Installation	For Maximum Humidity Output, Install on the Vertical Supply Plenum
Plenum Opening (Inches; HxW)	12.13 x 12.63
Pallet Quantity	30
Cabinet Construction	UV-Stable Automotive Grade Plastic
Humidistat	GFX5 (GFI# 7172)
Voltage (Volts)	120
Warranty (Years)	5
In The Box	Humidifier, GFX5 Humidistat, Solenoid Valve, Vapor Pad*, Installation Instructions, Mounting Template, Parts Kit With Push-to-Connect Valve.



Contractor Friendly



The Hinged Cover Means Not Having To Lift A Heavy Fan and Motor to Change the Vapor Pad.

Accessories



GFX5 (GFI #7172)
 Automatic Humidistat
 (Included)



Designed & Assembled
 in North America

Spec Sheet

Model 4400A Fan-Assist Evaporative Humidifier Features:

- Patented design
- 19 GPD
- Removable, hinged door for easy maintenance
- Stainless steel water distribution tube for hot water supply
- Suitable for up to a 4,400 sq. ft. home
- Quiet Cross-Flow Fan
- Safety shut-off switch
- UV-stable automotive-grade plastic cover and chassis
- Low-profile space-saving design
- GFX5 digital automatic humidistat



Vertical Supply Plenum Installation

Installation:

For maximum humidity output, install on the vertical supply plenum of any forced air furnace.

Maintenance:

Change the GA35 Vapor Pad® (GFI #7902) at least once per year.

1 Lift off the Cover



2 Swing the Door Open




3 Replace the Vapor Pad®



Product Support:

- www.generalaire.com
 - Installation Manual
 - Home Owner Brochure
 - 4400 Features Video
- Tech Support (866) 476-5101



Hinged Door Safety
 Shutoff Switch



- Drain Spout Can Be
 Removed for Cleaning
- Simply Slide Out