

DSH-2

240V Humidity Device Station

The TrolMaster DSH-2 Humidity 240V Device Station modules allow the user to easily connect and control standard humidifying or dehumidifying devices to the Hydro-X. The DSH modules are rated @ 10-amps.

***Caution:** Use DSH-2 with dehumidifiers less than 7 amps to avoid current overload.



Specifications

DSH-2

Input Voltage

Voltage 100-240V~, 50/60Hz

Output Current

Current 10A

Output Voltage

Voltage 100-240V~, 50/60Hz

Working Environments

Temperature 32-122°F (0-50°C)

Humidity ≤90%

Package Content

240V Humidity Device Station 1pc

16ft RJ12 Cable 1pc

4ft RJ12 Cable 1pc

RJ12 T-Splitter 1pc

Package Dimensions

Size 3.35inch / 85mm (L) x 3.15inch / 80mm (W) x 3.54inch / 90mm (H)

Gross Weight 12.0oz / 340g

LED Indicator Status

LED Indicator	Module Status
Fast Blinking Green	Module is not addressed to the main controller, OR module does not have a good connection to the main controller. *Note: Pressing the small address/link button on the module when first installed.
Slow Blinking Green	Module is addressed and connected to the main controller, and is currently turned OFF.
Solid Green	Module is addressed, connected, and main currently turned ON.
Blinking Red	Module is overloaded. Reset the overload by unplugging the module from powersource .

Link Up

DSH-2

CONNECTION DIAGRAM

