

IW25-5 In Wall/On Wall Dehumidifier With Bi-Polar Ion Generator

Product Specifications

IN WALL DIMENSIONS	
In Wall Base Unit	27.625" x 14.25" x 5.75"
In Wall Unit/Cover	30.375" x 17.25" x 7.25"
Rough Opening	28" x 14.5" x 5.75"
Exterior Sleeve	30.5" x 17.5" x 2.2"
ON WALL DIMENSIONS	
On Wall Base Unit	27.625" x 14.25" x 5.75"
On Wall Unit/Cover	27.625" x 14.25" x 7.25"
Keyhole Mount Distance	3.125"
PERFORMANCE	
Weight	39 lbs.
Spaced For	1,500 sq. ft.
Air Flow	155 cfm
Sound Pressure Level	46 dBA
Functioning Temperature Range	46-95°F
Functioning Relative Humidity Range	36-90%
Rated Condensation Capacity	Up to 33 PPD @ 80°F/60% RH
Warranty	5 Years on Parts & Labor
Energy Star Listing @ 65F/60%	21 PPD with @ 1.65 COP
ELECTRICAL	
Drain Connection Length	8'
Drain Connection Diameter	¾" Hose
Refrigerant	R32 – 0 Ozone Emissions
ELECTRICAL	
Volt Frequency	120 VAC/60 Hz
Rated Average Power Consumption	300 Watts @ 80°F/60% RH
Max Power Consumption	440 Watts @ 90°F/95% RH
Max Absorbed Current F.L.A.	2.8 Amps @ 80°F/60% RH
Locked Rotor Current L.R.A.	14 Amps
ION GENERATOR	
Ion Output	3,000,000/cc
Test Condition	20Cm; Wind Speed 1m/s
Ion Type	Bi-Polar/Positive and Negative Ions
Input Voltage	DC 24. 0V±0.1V

NOTE: Specifications subject to change without notice.

