

## Climate Pro® X Series

The cooler choice for your warehouse or factory.

The Climate Pro X Series brings advanced spot-cooling to commercial and industrial applications — perfect for cooling people and production processes.

### KEY FEATURES

- Air-cooled units from 13,200 to 24,000 Btu/h to handle temps as high as 113°F.
- Three-speed fan and adjustable nozzles for versatile cooling comfort.
- Digital controls and auto operation for 24/7 programmable back-up of central systems.
- Effective moisture removal hastens drying for humid and water-damaged areas.
- Connectivity ready with remote monitoring, geolocation and performance notifications.\*

*\*Subscription required, see your local dealer for details.*



*Roll it in. Set it up. Turn it on.*

### Ideal for . . .

Warehouses	Construction Sites
Assembly Lines	Moisture Removal
Manufacturing Plants	Special Events
Process Cooling	

Another line of quality products by DENSO.

**DENSO**



## Climate Pro® X Series Specifications

		X14e	X20e	X26e
Electronic Features	Control Panel	Programmable	Programmable	Programmable
Cooling Capacity	Rating Conditions: 95°F @ 60% RH	13,200 Btu/h	16,800 Btu/h	24,000 Btu/h*
Energy Efficiency Ratio (EER)		11.2	10.5	10.0
Electrical Characteristics	Voltage Requirement (60 Hz)	1 Phase, 115 V	1 Phase, 115 V	1 Phase, 208/230 V
	Total Power Consumption	1.2 kW	1.6 kW	2.3 kW*
	Current Consumption	11 amps	14.5 amps	10.6 amps*
	Recommended Fuse Size	15 amps	20 amps	20 amps
	NEMA Plug Configuration	5-15P	5-20P	6-20P
	Min. Max. Voltage	104 – 127 V	104 – 127 V	198 – 253 V
Fans	Motor Output	0.23 kW	0.37 kW	0.56 kW
Evaporator	Fan Type	Centrifugal	Centrifugal	Centrifugal
	Max Air Flow (high/mid/low)	440 / 410 / 385 CFM	565 / 525 / 475 CFM	700 / 650 / 595 CFM*
	Max External Static Pressure	0.31 IWG	0.31 IWG	0.42 IWG
Condenser	Fan Type	Centrifugal	Centrifugal	Centrifugal
	Max Air Flow (high/mid/low)	830 / 770 / 720 CFM	1000 / 930 / 830 CFM	1390 / 1280 / 1180 CFM*
	Max External Static Pressure	0.19 IWG	0.23 IWG	0.25 IWG
Compressor	Type	Hermetic Rotary	Hermetic Rotary	Hermetic Rotary
	Output	0.7 kW	0.75 kW	1.3 kW
Refrigerant	Type	R-32	R-32	R-32
	Amount	0.97 lb	1.12 lb	2.12 lb
Dimensions	W x D x H	22 x 29 x 48 in	22 x 29 x 51 in	22 x 29 x 51 in
Net Weight/Shipping Weight		177 / 216 lb	192 / 234 lb	219 / 255 lb
Power Cord	Gauge	14 AWG (3-core)	12 AWG (3-core)	12 AWG (3-core)
	Length	10 ft	10 ft	6 ft
Condensate Tank Capacity (approx.)		5 gal	5 gal	5 gal
Operating Conditions	Min. – Max. @ 50% RH	70° – 113°F	70° – 113°F	70° – 113°F
Max. Duct Length	Per Cold Duct Hose	30 ft	30 ft	60 ft
	Hot Duct Hose	60 ft	60 ft	45 ft
Max. Sound Level (high/mid/low)	With Condenser Duct	60 / 59 / 58 dB(A)	67 / 66 / 65 dB(A)	69 / 68 / 67 dB(A)
	Without Condenser Duct	60 / 59 / 58 dB(A)	67 / 66 / 65 dB(A)	69 / 68 / 67 dB(A)

\*Specifications information shown with 230 V. All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit [MovinCool.com/warranty](http://MovinCool.com/warranty) for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

DENSO Products and Services Americas, Inc.  
 3900 Via Oro Avenue | Long Beach CA 90810 USA  
 +1-800-264-9573 | [MovinCool.com](http://MovinCool.com)

