nextlight [PLUS] PRO SERIES













WET RATED IP65
















Package Contents

- 1 Fixture with Attached DC Out Power Cord (2') x1
- 2 Driver x1
- 3 Fixture Hooks x2
- 4 Driver Hooks x2
- 5 NextLight Pro Series Power Cord (9.75') x1 (see available Power Cord Voltage Options)
- 6 NextLight Pro Series Control Cable (20') x1



Power Cord Voltage Options











Product Dimensions

Fixture Dimensions







Technical Specifications

SPECIFICATION	NEXTLIGHT PLUS PRO
Operating Voltage	120-277 VAC
Operating Frequency	50/60 Hz
Input Current	2.67A @ 120V, 1.34A @ 240V, 1.16A @ 277\
PPF	800
Energy Use	320 Watts (305W @ 277V)
PPF/Watt	2.6
Operating Temperature	-4°F to 104°F (-20°C to 40°C)
BTU Output	1100
Fixture Dimensions (in/mm)	28.75 x 3.5 x 4.5 / 726.7 x 85.9 x 111.7
Driver Dimensions (in/mm)	14.75 x 5 x 2.25 / 374 x 124.4 x 54.5
Weight	17 lbs (7.71 kg)
Warranty	5 Year Full
Life Rating	Q90 > 50,000 Hours
Certifications	DLC Hort, CE, UL 8800
Environment	IP65, Wet Rated

Driver Dimensions





NextLight Full Spectrum LED

NextLight fixtures emit a full spectrum, bright white light which is more sun-like than even your traditional HPS. Using this spectrum you can expect tighter internodal spacing and better overall quality.

NextLight's Full Spectrum is easy to work under and provides the same sun-like qualities plants love without the negatives of high energy requirements and high heat.

