



# THROUGH-THE-WALL AIR CONDITIONER

12,000 BTU | ELECTRONIC




**6PATW12000**

|                                      |                                                                                                     |
|--------------------------------------|-----------------------------------------------------------------------------------------------------|
| <b>UPC CODE</b>                      | 842149002251                                                                                        |
| <b>COOLING CAPACITY (BTU)</b>        | 12000                                                                                               |
| <b>ENERGY STAR</b>                   | No                                                                                                  |
| <b>COVERAGE AREA (sq. ft.)</b>       | 550                                                                                                 |
| <b>CEER</b>                          | 10.5                                                                                                |
| <b>VOLTAGE</b>                       | 115V                                                                                                |
| <b>AMPS</b>                          | 11.3                                                                                                |
| <b>WATTS</b>                         | 1140                                                                                                |
| <b>FAN SPEEDS (cool/fan)</b>         | 3/3                                                                                                 |
| <b>UNIT DIMENSIONS (W×H×D) (in.)</b> | 24.25×14.25×20.25                                                                                   |
| <b>PKG. DIMENSIONS (W×H×D) (in.)</b> | 28×17×27                                                                                            |
| <b>WEIGHT (Net/Gross) (lbs.)</b>     | 76/88                                                                                               |
| <b>CONTAINER QTY. (40HQ)</b>         | 306                                                                                                 |
| <b>REFRIGERANT</b>                   | R32                                                                                                 |
| <b>OUTLET CONFIGURATION</b>          | <br>15A - 115V |

## CHOOSING THE RIGHT AIR CONDITIONER

### 1 MEASURE AREA OF THE ROOM



### 2 MATCH ROOM SIZE WITH CORRECT BTUs

| SQ. FT. | ROOM SIZE | BTUs   |
|---------|-----------|--------|
| 150     | 10' × 15' | 5,000  |
| 250     | 10' × 25' | 6,000  |
| 350     | 17' × 20' | 8,000  |
| 450     | 15' × 30' | 10,000 |
| 550     | 20' × 27' | 12,000 |
| 700     | 20' × 35' | 15,000 |
| 1,000   | 25' × 40' | 18,000 |
| 1,500   | 30' × 50' | 25,000 |

### 3 MAKE ANY ADJUSTMENTS



**INCREASE BTU 10%**  
FOR SUNNY ROOMS. DECREASE  
BTU 10% FOR SHADED ROOMS.



**ADD 600 BTUs**  
FOR EACH ADDITIONAL  
PERSON OVER TWO.



**ADD 4,000 BTUs**  
IF UNIT IS USED IN  
A KITCHEN.

## FEATURES

- Fits most standard through-the-wall AC sleeves
- 3 cooling & 3 fan speeds
- 4-way adjustable air vents
- Cool, Fan, Eco, and Sleep modes
- Quick & easy installation
- Mounting kit included
- Electronic controls
- Follow-me remote control acts as portable thermostat
- 24-hour timer
- Auto-restart
- Adjustable thermostat (62-86°F)
- Easy clean slide out filter

