


AL 630 D4 01

154152


ruck

- Innovative, high-efficiency axial fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing weight optimized, powder coated
- Efficient IE3 motor, frequency controllable
- Conveyed medium temperature up to 60 °C in continuous operation
- Exceeds current ErP regulation by 15 - 20%



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		$W \times H_{\text{duct}}$
Pipe connection size (DN)	DN630		DN
Rated voltage (entire device)	400	V	U_{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	10 A		fuse
Housing material	Coated steel		$\text{mat}_{\text{casing}}$
Impeller material	Coated steel		$\text{mat}_{\text{impeller}}$
IP-protection class (entire device)	IPX4		IP_{compl}
IP-Protection class (terminal box)	IP55		IP_{ebox}
Weight	65.2	kg	m
Fan type	Axial		Fan_{type}
Category / Installation situation	B		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	5680	W	$P_{\text{ed, max}}$
Max. operating current (device)	9.1	A	$I_{\text{ed, max}}$
Max. speed	1910	1/min	n_{max}
Max. stat. efficiency	56.6	%	η_{es}
Max. fan efficiency	68.9	%	η_{e}
Max. flowrate	24620	m³/h	$Q_{\text{v, max}}$
Max. stat pressure	625	Pa	$p_{\text{sf, max}}$
Max. medium temperature	60	°C	$T_{\text{m, max}}$
Max. environment temperature	60	°C	$T_{\text{amb, max}}$
Min. environment temperature	-20	°C	$T_{\text{amb, min}}$




to the product detail page

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwrsupmotor
Number of poles (1)		4.000000		num polesw1
Connection	Δ	Y		wiringw1
Connection (wiring 2)	Y			wiringw2
Rated voltage	230	460	V	U _{rated, f1}
Rated voltage (wiring 2)	400		V	U _{rated, f2}
Rated current	14.3	7.28	A	I _{rated, f1}
Rated current (wiring 2)	8.2		A	I _{rated, f2}
Shaft power	4000	4000	W	P _{out, f1}
Shaft power (wiring 2)	4000		W	P _{out, f2}
Speed	1450	1755	1/min	n _{f1}
Speed (wiring 2)	1450		1/min	n _{f2}
Starting current	100	58.2	A	I _{start, f1}
Starting current (wiring 2)	57.4		A	I _{start, f2}
Efficiency	89.1	89.5	%	η _{m, f1}
Efficiency (wiring 2)	89.1		%	η _{m, f2}
Efficiency class	IE3	IE3		IE _{motor}
Min. temperature	-20	-20	°C	T _{motor, min}
Cos Phi	0.790000	0.770000		cos φ
UL-Certification motor		UL recognized		ULcert




CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



AL 630 D4 01

154152


ruck



to the product detail page


AL 630 D4 01

154152




to the product detail page

AL 630 D4 01
154152



AL 630 D4 01

154152



to the product detail page

MECHANICAL ACCESSORIES

RVK 630 | 153910



- Automatic tube shutter
- Sheet steel, powder coated
- For vertical installation
- Flange mounting

RVK H 630 | 155488



- Automatic tube shutter
- Sheet steel, powder coated
- For horizontal installation
- Flange mounting

RVS 630 01 | 154198



- Tube connection spigot
- Sheet steel, powder coated
- Suitable for outdoor installation
- Flange mounting

ESD 630 | 153942




- Inlet cone
- Steel sheet, powder coated
- Flange mounting

FAL 630 | 154811



- Mounting foot
- Sheet steel, powder coated

SGW 710 | 154056




- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

FSD 03 | 155500




- Set of 4 vibration dampers
- All metal design, galvanized

SGW 630 | 154054



- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

SGE 630 | 154079



- Protection grille, narrow meshed
- Steel sheet, galvanized
- Flange mounting

RAF 630 | 154023



- Round flange
- Sheet steel, powder coated

RAS 630 | 154252



- Round spigot, flexible
- Galvanized steel sheet, plastic band (PES)
- Temperature resistant up to 75 °C
- Flange mounting

FSD 06 | 155503



- Set of 4 vibration dampers
- Made of natural rubber, hardness 55 Shore A

MR 630 | 165852



- Mounting ring
- For vertical mounting
- Powder-coated sheet steel
- Flange mounting DN 630



ELECTRICAL ACCESSORIES

MS 04 | 140413



- Motor protection switch with Isolator switchfunktion
- I_{max} = 400 V, 50/60 Hz
- Max. 4 kW
- Protection class IP 55

MTP 20 | 128146



- Potentiometer 10 kΩ
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 kΩ
- Step 1 + 2 settable 10 % - 100 % V_{dc}
- Step 3 100 % V_{dc}
- Supply voltage +10 V_{dc}

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature 0...+50 °C
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

FU 55 15 | 155178



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Protection class IP 20, for switch cabinet

FU 55 16 | 155179



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Fire mode function (smoke extract fans)

GS 02 | 169671



- Isolator switch
- U_{max} = 400 V, 50/60 Hz
- Switching capacity 400 V 3~ = 7,5 kW
- I_{max} = 25 A

