








4" MAKE-UP AIR INTAKE



N.T.S.




DAMPER CLOSSES AGAINST
CLOSED CELL FOAM GASKET



UNIT WEIGHT: 1lb 12oz or 1.56lbs


Included with kit



Stud mount transformer

UNIT WEIGHT: 14oz
2.25"L x 2"W x 2.5"H

UL® Listed:
Input: 120 VAC, 60Hz
Output: 24VAC, 60Hz, 15VA



Current Switch

UNIT WEIGHT: 3oz
1"L x 3.5"W x 2.5"H




UL® Listed:
Input AC
120 VAC, 60Hz, 0.5 - 200A
Switching (max)
0.3A at 135V (AC/DC)
Max Ambient Temp:
140°F(60°C)

- Kit allows automatic operation when range hood or exhaust fan is activated
 - Less than 5% air leakage when damper is fully closed
 - Normally Closed - Power Open, Spring Return
 - 6 Running Watts, 0.25 Amps, 24 VAC, 60 Hz
 - Max Torque: 78in.-oz
- Mounting Hardware Included:**
(6) #6 Sheet metal screws

MODEL: ZCMU04





5" MAKE-UP AIR INTAKE




N.T.S.

DAMPER CLOSSES AGAINST
CLOSED CELL FOAM GASKET



UNIT WEIGHT: 1lb 15oz or 1.9lbs


Included with kit



Stud mount transformer

UNIT WEIGHT: 14oz
2.25"L x 2"W x 2.5"H

UL® Listed:
Input: 120 VAC, 60Hz
Output: 24VAC, 60Hz, 15VA



Current Switch

UNIT WEIGHT: 3oz
1"L x 3.5"W x 2.5"H


UL® Listed:
Input AC
120 VAC, 60Hz, 0.5 - 200A
Switching (max)
0.3A at 135V (AC/DC)
Max Ambient Temp:
140°F(60°C)

- Kit allows automatic operation when range hood or exhaust fan is activated
 - Less than 5% air leakage when damper is fully closed
 - Normally Closed - Power Open, Spring Return
 - 6 Running Watts, 0.25 Amps, 24 VAC, 60 Hz
 - Max Torque: 78in.-oz
- Mounting Hardware Included:**
(6) #6 Sheet metal screws



MODEL: ZCMU05





6" MAKE-UP AIR INTAKE



N.T.S.




DAMPER CLOSSES AGAINST
CLOSED CELL FOAM GASKET



UNIT WEIGHT: 2lb 3oz or 2.1lbs


Included with kit



Stud mount transformer

UNIT WEIGHT: 14oz
2.25"L x 2"W x 2.5"H

UL® Listed:
Input: 120 VAC, 60Hz
Output: 24VAC, 60Hz, 15VA



Current Switch

UNIT WEIGHT: 3oz
1"L x 3.5"W x 2.5"H

UL® Listed:
Input AC
120 VAC, 60Hz, 0.5 - 200A
Switching (max)
0.3A at 135V (AC/DC)
Max Ambient Temp:
140°F(60°C)

- Kit allows automatic operation when range hood or exhaust fan is activated
 - Less than 5% air leakage when damper is fully closed
 - Normally Closed - Power Open, Spring Return
 - 6 Running Watts, 0.25 Amps, 24 VAC, 60 Hz
 - Max Torque: 78in.-oz
- Mounting Hardware Included:**
(6) #6 Sheet metal screws

MODEL: ZCMU06




8" MAKE-UP AIR INTAKE



24 GAUGE
STEEL
HOUSING


2.00" DIA.




8.0in (203mm)

20 GAUGE
STEEL BLADE

3.1in (78mm)




DAMPER CLOSSES AGAINST
CLOSED CELL FOAM GASKET



2.8in
(71mm)


11.0in (178mm)



2 WIRE
HYSTERESIS
GEAR MOTOR

UNIT WEIGHT: 3lb 2oz or 3.1lbs


Included with kit



Stud mount transformer

UNIT WEIGHT: 14oz
2.25"L x 2"W x 2.5"H

UL® Listed:
Input: 120 VAC, 60Hz
Output: 24VAC, 60Hz, 15VA



Current Switch

UNIT WEIGHT: 3oz
1"L x 3.5"W x 2.5"H


UL® Listed:
Input AC
120 VAC, 60Hz, 0.5 - 200A
Switching (max)
0.3A at 135V (AC/DC)
Max Ambient Temp:
140°F(60°C)

- Kit allows automatic operation when range hood or exhaust fan is activated
 - Less than 5% air leakage when damper is fully closed
 - Normally Closed - Power Open, Spring Return
 - 6 Running Watts, 0.25 Amps, 24 VAC, 60 Hz
 - Max Torque: 78in.-oz
- Mounting Hardware Included:**
(6) #6 Sheet metal screws

MODEL: ZCMU08



10" MAKE-UP AIR INTAKE



N.T.S.

24 GAUGE
STEEL
HOUSING

2.00" DIA.



8.0in (203mm)

20 GAUGE
STEEL BLADE

3.1in (78mm)


ø10in (102mm)

DAMPER CLOSSES AGAINST
CLOSED CELL FOAM GASKET



UNIT WEIGHT: 3lb 15oz or 3.9lbs


Included with kit



Stud mount transformer

UNIT WEIGHT: 14oz
2.25"L x 2"W x 2.5"H

UL® Listed:
Input: 120 VAC, 60Hz
Output: 24VAC, 60Hz, 15VA



Current Switch

UNIT WEIGHT: 3oz
1"L x 3.5"W x 2.5"H


UL® Listed:
Input AC
120 VAC, 60Hz, 0.5 - 200A
Switching (max)
0.3A at 135V (AC/DC)
Max Ambient Temp:
140°F(60°C)

- Kit allows automatic operation when range hood or exhaust fan is activated
 - Less than 5% air leakage when damper is fully closed
 - Normally Closed - Power Open, Spring Return
 - 6 Running Watts, 0.25 Amps, 24 VAC, 60 Hz
 - Max Torque: 78in.-oz
- Mounting Hardware Included:**
(6) #6 Sheet metal screws



MODEL: ZCMU10





12" MAKE-UP AIR INTAKE



N.T.S.




DAMPER CLOSSES AGAINST
CLOSED CELL FOAM GASKET



UNIT WEIGHT: 4lb 11oz or 4.7lbs


Included with kit



Stud mount transformer

UNIT WEIGHT: 14oz
2.25"L x 2"W x 2.5"H

UL® Listed:
Input: 120 VAC, 60Hz
Output: 24VAC, 60Hz, 15VA



Current Switch

UNIT WEIGHT: 3oz
1"L x 3.5"W x 2.5"H

UL® Listed:
Input AC
120 VAC, 60Hz, 0.5 - 200A
Switching (max)
0.3A at 135V (AC/DC)
Max Ambient Temp:
140°F(60°C)

- Kit allows automatic operation when range hood or exhaust fan is activated
 - Less than 5% air leakage when damper is fully closed
 - Normally Closed - Power Open, Spring Return
 - 6 Running Watts, 0.25 Amps, 24 VAC, 60 Hz
 - Max Torque: 78in.-oz
- Mounting Hardware Included:**
(6) #6 Sheet metal screws

MODEL: ZCMU12