

Airpura

AIR PURIFIERS

I700

THE PURIFIER FOR HEALTHCARE PROVIDERS PLUS

ISOLATION, PARTICLE ABATEMENT
UV OPTION FOR ANTIGEN AND PATHOGEN
STERILIZATION

THE AIRPURA I700
Available in White / Black / Cream

THE AIRPURA LIMITED WARRANTY
5 years parts / 10 years labor



THE AIRPURA I700 SPECIALLY DESIGNED FOR USE IN HEALTHCARE CLINICS AND INSTITUTIONS.


- **HEPA FILTER CLOSE ENDED METAL CAPPED** that captures 99.97% of particles as small as 0.3 microns.
- **OPTIONAL HI-C CARBON WEAVE** Adsorbs light odors, VOC's, chemicals.
- Effective for up to **2,000 SQUARE FEET**. Provides a complete air exchange every 30 minutes.
- **OPTIONAL NEGATIVE AIR ACCESSORIES AVAILABLE**. Enables you to quickly create an isolation area.
- **SOLID EASY TO MOVE, LOCKABLE CASTERS**. Weighs less than 30 lbs. Moves easily and casters can be locked in place.

HIGH QUALITY HEPA FILTER

Over 100 square feet of filtration surface with 3" deep folds.

The Hepa is warm rolled to avoid cracking at the folds and avoid leakage.

Spacers keep the folds open and make sure that all the surface area is filtering.



FILTER LIFE



HEPA FILTER
should be replaced
between 3 and 5
years (depending
on use).




**OPTIONAL
HI-C CARBON
WEAVES** should be
replaced every 4-6
months, depending
on use.



PREFILTER should
be replaced every
12 months.

EXPERIENCE THE EVOLUTION OF CLEAN AND HEALTHY AIR

FILTRATION SYSTEM



UNIQUE FEATURES

PRESSURE SEAL Airpura's unique pressure seal on the filter chamber along with close ended metal caps on the HEPA filter ensures that all of the dirty air passes through the filters. Other systems allow leakage and do not achieve the 99.97% HEPA filtration rating.

FELT GASKETS seal the filter chamber. Maximize filtration with no rubber off-gassing found with other filters.

BACKWARD CURVED MOTORIZED IMPELLER eliminates the vibrations and noise associated with older motor and shaft set ups

VARIABLE SPEED MOTOR lets you choose your ideal level of filtration.

MOTOR OUT OF THE AIR FLOW. Most air purifiers blow the clean air over the motor and pick up fresh impurities

UNIMPEDED AIRFLOW simple and direct internal airflow avoids the air turbulence, inefficiency and noise associated with more convoluted systems

SEPARATE ELECTRICAL PARTS CHAMBER prevents any off gassing from capacitors, condensers or switches.

PERFORATED STEEL EXTERIOR offers both a softer appearance and 360 degree air intake and distribution.

TECHNICAL SPECIFICATIONS

PARTICLE REMOVAL Over 100 sq ft true HEPA (Measured only 1 side) with close ended metal caps. 10 pleats per inch. Warm rolled with separators

635 CFM

PREFILTER
570 sq in x 1 in

HOUSING
Powder coat steel

SIZE
23" x 15"

WEIGHT
29 lbs total

VOLTAGE OPTIONS
115 or 220 volts

WATTS
120 on high / 40 on low

SOUND LEVEL
30.2 db on low (at 6 feet)
63.0 db on high (635 cfm)

ETL CERTIFIED
Conforms to CSA C22.2
no 113 ANSI / UL 507

YOUR
AIRPURA™ DEALER

